



VANBERG SPECIALIZED COATINGS
 PO BOX 19414 □ LENEXA, KS 66285-9414
 (800) 874-0631 □ (913) 599-5939 □ FAX: (913) 599-5949
 Web: vanbergcoatings.com □ Email: vsc@vanbergcoatings.com

VSC PRODUCT LIST
 March 1, 2008

PRODUCT LISTING

FOR COATING SYSTEMS AND PRODUCT DETAILS, PLEASE REFER TO THE APPROPRIATE PRODUCT DATA SHEET OR SYSTEM APPLICATION GUIDE

MOST VSC COATINGS MEET USDA GUIDELINES FOR FEDERALLY INSPECTED FACILITIES

HIGH BUILD HIGH-PERFORMANCE COATINGS

EPOXY COATINGS

ARMORCOAT BASE CLEAR or MEDIUM GRAY High build 100% solids epoxy coating is ideal for your toughest environments. Excellent gloss, chemical resistance and color stability. Can be combined with VSC aggregates.	140 sq ft/gal @ 12 mils	1.5 gal kit (clear)	AC133	15 lbs
	80 sq ft/gal @ 20 mils	3 gal kit (clear)	AC133-3	30 lbs
	Clear accepts VSC colorants	15 gal kit (clear) ☹	AC133-15	145 lbs
		1.5 gal kit (medium gray)	AC133G	16 lbs
		3 gal kit (medium gray)	AC133G-3	32 lbs
15 gal kit (medium gray) ☹	AC133G-15	150 lbs		
ARMORCOAT MV EPOXY CLEAR or MEDIUM GRAY Medium viscosity version of Armorcoat Base has excellent leveling properties. It is the best topcoat choice for VSC overlay systems. It also works great as a medium build (10-20 mils) coating system.	140 sq ft/gal @ 12 mils	1.5 gal kit (clear)	AC310MV	15 lbs
	160 sq ft/gal @ 10 mils	3 gal kit (clear)	AC310MV-3	30 lbs
	400 sq ft/gal @ 4 mils – as sealer. Extend with SOLVENT 101 - clear only (use 1 gal solvent per 3 gal kit)	15 gal kit (clear) ☹	AC310MV-15	150 lbs
		1.5 gal kit (medium gray)	AC310MVG	16 lbs
		3 gal kit (medium gray)	AC310MVG-3	32 lbs
15 gal kit (medium gray) ☹	AC310MVG-15	155 lbs		
ARMORCOAT FAST EPOXY (LRS) CLEAR or MEDIUM GRAY Fast setting version of Armorcoat Base best for a fast turnaround. Ready for light traffic in 4-5 hours. Excellent durability and chemical resistance. Can be combined with VSC aggregates.	140 sq ft/gal @ 12 mils	1.5 gal kit (clear)	AC210-380	16 lbs
	Clear accepts VSC colorants	3 gal kit (clear)	AC210-380-3	32 lbs
		15 gal kit (clear) ☹	AC210-380-15	160 lbs
		1.5 gal kit (medium gray)	AC210-183VB	20 lbs
		3 gal kit (medium gray)	AC210-183VB-3	38 lbs
		15 gal kit (medium gray) ☹	AC210-183VB-15	190 lbs
2.5 gal kit (medium gray)	AC210-250G	34 lbs		
Harvestore pack				
EPOXY FLEX COAT CLEAR A tough, flexible, crack bridging coating that stands up to vehicular traffic. Very good gloss, chemical and stain resistance. Accepts colorants. Great for wood.	80-100 sq ft/gal @ 20-16 mils	2 gal kit (clear)	EF139-2	23 lbs
		10 gal kit (clear) ☹	EF139-10	115 lbs
EPOXY TEXTURE COAT Provides an orange peel texture. Clear, high build 100% solids epoxy. Very good gloss, chemical and stain resistance. Grout coat for Epo-Stone Flooring. Accepts colorants.	140 sq ft/gal @ 12 mils	3 gal kit (clear)	82094-3	35 lbs
		15 gal kit (clear) R	82094-15	170 lbs

HIGH CHEMICAL RESISTANT (CONTAINMENT) EPOXY COATINGS

NOVOLAC EPOXY CLEAR or MEDIUM GRAY Withstands a wide variety of acids, chemicals and solvents. High build 100% solids epoxy. Exhibits excellent wear-ability. Maintains a gloss finish.	100 sq ft/gal @ 16 mils	.61 gal kit (clear)	92600-60	7 lbs
		5 gal kit (clear) ☹	92600-5	48 lbs
		12.5 gal kit (clear) ☹	92600-12.5	134 lbs
		.65 gal kit (medium gray)	92600G-60	8 lbs
		5.1 gal kit (medium gray) ☹	92600G-5	56 lbs
		12.7 gal kit (medium gray) ☹	92600G-12.7	138 lbs
NOVOLAC MV VSC Novolac epoxy has a high resistance to UV light exposure and makes an ideal clear topcoat.	100 sq ft/gal @ 16 mils	2.5 gal kit (clear)	92602-2.5	24 lbs

HIGH-PERFORMANCE COATINGS & SEALERS

WATER-BASED EPOXIES

EPO-SEAL WB EPOXY-FAST Low odor, high-penetration, fast-setting clear water-based epoxy primer/sealer/coating. Very good gloss, wear and chemical resistant properties. Moisture tolerant.	350 sq ft/gal @ 1.5 mils dry Apply two coats for uniform gloss	.75 gal kit	ES2300-75	10 lbs
		3 gal kit	ES2300-3	36 lbs
		15 gal kit R	ES2300-15	141 lbs
EPO-POXY HS CLEAR Water-based, high build epoxy with low odor and moisture tolerance. Very good gloss and wear properties.	250 sq ft/gal @ 4 mils dry Apply two coats for uniform gloss	.75 gal kit (clear)	ES016-75	10 lbs
		3 gal kit (clear)	ES016-3	36 lbs
		15 gal kit (clear) R	ES016-15	142 lbs
EPO-SEAL HS CLEAR or COLOR EPOXY Clear or Colored water-based epoxy coating. Has excellent adhesion properties and abrasion resistance. Odorless and non-flammable option to urethane coatings.	260 sq ft/gal @ 6 mils dry Apply two coats for uniform gloss	2 gal kit (clear)	ES015-2	20 lbs
		5 gal kit (clear)	ES015-5	45 lbs
		2 gal kit (color)	ES015C-2	24 lbs
		5 gal kit (color)	ES015C-5	27 lbs
WB ACRYLIC URETHANE Clear, water-based single component urethane. No urethane odor. Very good gloss and UV light resistance.	400 sq ft/gal @ 2 mils dry Apply two coats for uniform gloss	1 gal kit (clear)	ES031-1	10 lbs
		5 gal kit (clear)	ES031-5	50 lbs

SOLVENT-BASED EPOXIES

ARMORCOAT EPOXY 65 CLEAR or MEDIUM GRAY High-solids, fast setting colored primer/sealer/coating. Very good moisture and chemical resistance. Semi-gloss. Tough wearing properties. 65% solids. Medium gray. Other colors also available.	250 sq ft/gal @ 4 mils dry Apply two coats for uniform finish	2 gal kit (clear)	AC154-2	22 lbs
		10 gal kit (clear) ☹	AC154-10	110 lbs
		2 gal kit (color)	AC144-2	25 lbs
		10 gal kit (color) ☹	AC144-10	147 lbs
VSC CONCRETE SEAL Solvent based clear sealer with high penetration properties. Prevents salt pitting, staining and stops concrete dusting. Dries fast and doesn't discolor.	400 sq ft/gal (typical)	1 gal (clear) (4/case) ☹ 5 gal pail (clear) ☹	ES510-1 ES510-5	10 lbs 50 lbs

CHEMICAL RESISTANT ALIPHATIC URETHANES

ULTRA-GLOSS CRU CLEAR or MEDIUM GRAY Ultimate in gloss and color retention. High resistance to UV exposure, chemical attack, scratching and staining. Accepts color additives. Other colors available.	400 sq ft/gal @ 4 mils dry Apply over a prime coat of ARMORCOAT 65 or EPO-POXY HS	1.5 gal kit (clear)	UG321	15 lbs
		3 gal kit (clear)	UG321-3	30 lbs
		15 gal kit (clear) ☹	UG321-15	150 lbs
		1.5 gal kit (medium gray)	UG321C	15 lbs
		3 gal kit (medium gray)	UG321C-3	30 lbs
		15 gal kit (medium gray) ☹	UG321C-15	150 lbs

POLYASPARTICS

POLYASPARTIC LPL URETHANE Fast-setting clear 100% solids polyaspartic aliphatic urethane with extended pot life. Has excellent chemical resistance, hardness, and abrasion resistance. Exceptional UV stability.	25 sq ft/gal @ 62.5 mil (slurry) 160 sq ft/gal@10 mil (sealer)	2.6 gal kit (clear)	PA349-2.6	24 lbs
POLYASPARTIC LV URETHANE Fast-setting solvent based 66% solids polyaspartic clear urethane. This thin build coating has excellent chemical resistance, hardness, abrasion resistance, and UV stability. Extended working time.	400 sq ft/gal @ 4 mil	2 gal kit (clear) 10 gal kit (clear) R	PA341LV-2 PA341LV-10	20 lbs 100 lbs

OVERLAYS

EPO-STONE 1/4 INCH EPOXY MORTAR Trowel applied at 1/4" to any thickness. Extremely tough wearing chemical and impact resistant surface. Overlay, patch or cove. NOTE: Can pigment Natural (3 oz color additives per .5 gal kit) using VSC Color Additives. PRIMER: Use EPO-STONE AB LIQUIDS (roll-coat applied). SEAL COAT (Optional): Use EPO-STONE AB LIQUIDS (roll-coat applied) or an ARMORCOAT EPOXY (100% solids). FINAL TOPCOAT OPTIONS: TEXTURE COAT EPOXY or ARMORCOAT EPOXIES or OVERLAY systems.	<u>Base Mix:</u> EPO-STONE AB plus 35 lbs selected sand blend (hand trowel batch). Mixed mortar covers 16-18 sq ft @ nominal 1/4" thickness. <u>Prime:</u> EPO-STONE AB LIQUIDS (roll-coat applied) @ 75-100 sq ft per .5 gal unit. <u>Seal Coat:</u> Use EPO-STONE AB LIQUIDS (roll-coat applied) @ 75-100 sq ft per .5 gal unit.	EPO-STONE KITS: Hand trowel batch consists of .5 gal epoxy and 35 lbs ES NATURAL		
		GRAY KIT (5 gal pail)	82810-G	45 lbs
		NATURAL KIT (5 gal pail)	82810-N	45 lbs
		EPO-STONE AB Bulk Bag R Pack Unit contains (16) .5 gal Bag Pack units	82801-AB16	82 lbs
		COMPONENTS: EPO-STONE AB LIQUIDS .5 gal unit	82801-AB	8 lbs
		AGGREGATE BLENDS (options): 35 lb bag (order with liquids; <u>one bag</u> per .5 gal unit to make up the base mix)		
		ES NATURAL BLEND	82801-35N	35 lbs
		G-DIAMOND BLEND	82900-35N	35 lbs

<p>ARMOR-SLATE (AGGREGATE-FILLED) SYSTEM High build epoxy overlay with exceptional wear performance. Fills and levels rough and pitted surfaces. Smooth high gloss tile-like finish. Chemical and stain resistant.</p>	<p>Combine 1.5 gal of ARMORCOAT MV or ARMORCOAT FAST with up to 25 lbs VSC THIXO medium or fine aggregate to make a trowel applied self-leveling slurry. <u>Coverage:</u> (sq ft per 1.5 gal unit)</p>	<p><u>Agricultural:</u> Mangers Bunks Troughs/Gutters</p> <p><u>Industrial:</u> Manufacturing Food Processing Pharmaceutical</p>	<p><u>Topcoats:</u> Any VSC epoxy, urethane or system can be applied as needed to fit the application requirements.</p>
<p>ARMOR-ROCK (AGGREGATE FILLED EPOXY with AGGREGATE BROADCAST) SYSTEM</p> <p>High build epoxy overlay with exceptional impact resistance and wear performance. Non-slip uniform textured finish. Chemical and stain resistant. Trowel applied at 1/16" to 1/4" thickness followed by surface broadcast of selected VSC AGGREGATE at the rate</p> <p>TOPCOAT: A topcoat is optional for added gloss and ease of cleaning. ARMORCOAT EPOXIES are recommended at 80-100 sq ft/gal</p> <p>ARMOR-ROCK THX SYSTEM Combine 15 lbs THIXO finely ground aggregate to 1.5 gal of ARMORCOAT epoxy to produce a thick tough-wearing overlay. Can be applied from 1/32nd to 1/8th inch thickness. Smooth or non-slip.</p> <p>ARMOR-GROUT SYSTEM Combine 35 lbs. ES natural or G-Diamond aggregate with .5 gal (about 20 fl. oz. hardener and 40 fl. oz. resin) ARMORCOAT MV clear epoxy (1 batch) to produce a trowel-applied mortar for repairs and overlays.</p>	<p><u>ARMOR-ROCK systems:</u> For <u>coarse</u> textured surface, combine 1.5 gal of selected ARMORCOAT epoxy with 25 lbs ES NATURAL for base mix. Then broadcast 25 lbs selected VSC aggregate over the surface. Use ES NATURAL or G-DIAMOND aggregates.</p> <p>For a <u>medium</u> texture use #210-520B medium aggregate as an admix and broadcast.</p> <p>ARMOR-ROCK <u>Coverage</u> (sq ft per 1.5 gal unit): 21 sq ft @ 1/4" 28 sq ft @ 3/16" 42 sq ft @ 1/8"</p> <p>ARMOR-ROCK THX <u>Coverage</u> (sq ft per 1.5 gal unit): 60 sq ft @ 1/16th inch</p> <p>ARMOR-GROUT <u>Coverage</u> (sq ft per batch): 16-18 sq ft @ 1/4 inch</p>	<p><u>Coarse textured systems:</u> Livestock production Manufacturing where heavy-duty non-slip surfaces are required.</p> <p><u>Medium textured systems:</u> Manufacturing Pharmaceutical Food processing Milk storage Chemical rooms</p> <p>Troughs - Smooth Slats - Broadcast sand for non-slip</p>	<p><u>Topcoats:</u> High Build Armorcoat epoxies are recommended for most manufacturing and commercial applications.</p> <p>Typically, topcoats are not used for pork and dairy livestock traffic applications. Use topcoats where appearance and cleaning ease are important.</p>

<p>ARMOR-GRIT (AGGREGATE BROADCAST AB) SYSTEM</p> <p>Roll coat applied epoxy system with aggregate broadcast and topcoat that achieves a uniform textured surface. Exceptional high-wear, impact resistance and cleaning ease. 1/16-1/8" nominal thickness (typical). Apply over uniform concrete surfaces. NOTE: Th</p>	<p><u>BASE:</u> ARMORCOAT MV or ARMORCOAT FAST</p> <p>250 sq ft/1.5 gal kit (typical) with #210-520B or COLOR STONE broadcast at the rate of .3 to .5 lbs per sq ft.</p> <p><u>TOPCOAT:</u> ARMORCOAT MV or ARMORCOAT FAST @ 120-150 sq ft/1.5 gal kit</p> <p>NOTE: A single base and topcoat combine to form a 1/16th inch overlay. A second base coat with broadcast is required for a 1/8th inch overlay.</p>	<p>See VSC AGGREGATES for aggregate broadcast options and prices.</p>	<p>ARMOR-GRIT systems require .3 to .5 lbs aggregate surface broadcast per sq ft (smooth surfaces .3 lbs and rough surfaces up to .5 lbs).</p> <p>For a <u>coarse</u> textured surface, use ES NATURAL or G-DIAMOND aggregates.</p> <p>For a <u>medium</u> textured surface use #210-520B MEDIUM aggregate or VSC COLOR STONE.</p> <p>For <u>fine</u> systems use #210-540 FINE as the broadcast aggregate.</p>
---	--	---	---

VSC AGGREGATES, ADDITIVES & CATALYST

USE VSC FINE SANDS for LIGHT TRAFFIC non-slip.

USE #30 G-DIAMOND, #390 or VSC BLENDS for HEAVY TRAFFIC for large LIVESTOCK non-slip.

<p>AGGREGATE BROADCASTS</p> <p>Light broadcasts are aggregates that are sprinkled over wet epoxy and then re-rolled to encapsulate. They produce a slight non-slip surface. For coarse broadcasts, see Aggregate Blends (below).</p> <p>Full broadcasts are aggregates that are broadcast over wet epoxy until the surface is completely saturated with the aggregate (no wet spots).</p>	<p><u>LIGHT BROADCAST</u> .01 lbs per sq ft for light non-slip texture</p> <p><u>FULL BROADCAST</u> .3-.5 lbs per sq ft for uniform tough-wearing non-slip surface (ARMOR-GRIT) or up to 1 lb per sq ft for overlays (ARMOR-ROCK)</p>	<p><u>#210-520B MEDIUM</u> For HIGH BUILD COATINGS applied @ 100-150 sq ft/gal</p> <p><u>#210-540 FINE</u> For coatings applied @ 150-300 sq ft/gal</p> <p><u>COLOR STONE decorative aggregate</u> (see chart for options)</p> <p>Solid color (medium) ES502 Color blends (medium) ES502B <u>COLOR FLAKES</u> (see chart for options)</p> <p>Solid color ES602-10 ES602-55 Blends ES602B-10 ES602B-55</p>	<p>210-520B 50 lbs</p> <p>210-540 50 lbs</p> <p>50 lbs</p> <p>50 lbs</p> <p>10 lbs</p> <p>55 lbs</p> <p>10 lbs</p> <p>55 lbs</p>	
<p>AGGREGATE BLENDS for ADMIX and BROADCASTS</p>	<p>One bag per .5 gal kit of EPO-STONE AB for a trowel applied mortar or 25 lbs per 1.5 gal kit of ARMORCOAT EPOXY for a trowel applied slurry</p> <p>See LIGHT and FULL BROADCAST coverage rates above</p>	<p><u>ES NATURAL BLEND</u> (coarse)</p> <p>Natural color high wear blend</p> <p><u>G-DIAMOND NATURAL BLEND</u> (coarse) Formulated for extended wear</p>	<p>82801-35N 35 lbs</p> <p>82801-50N 50 lbs</p> <p>82900-35N 35 lbs</p>	

COLOR ADDITIVES Color additive packs for most clear epoxies and urethanes.	USAGE: 1 qt/3 gal to color top coats and 1/2 qt/3 gal to tint base coats	White*	CA002	4 lbs each
	*Use 2 qts/3 gal for light or bright colors in top coats	Black	CA003	
Use 3 fl oz per batch (.5 gal kit) of EPO-STONE AB with Natural or G-Diamond aggregate blends to color EPO-STONE MORTAR	1 QT UNITS, 4/CS	Rust	CA004	
		Medium Gray	CA007	
		Charcoal	CA009	
		Tile Red	CA010	
		Mocha	CA011	
		Green	CA012	
		Light Blue	CA013	
		Blue	CA014	
		Dark Blue	CA015	
		Sandstone*	CA016	
		Beige	CA017	
		Chocolate	CA018	
		Buff*	CA019	
		Safety Yellow (ANSI)*	CA020	
		Tan*	CA029	
		Steel Gray	CA031	
THIXO Thickening additive for 100% solids epoxies. Reduces slump.	Variable (typically 5-10 lbs per gallon)	10 lb pail 50 lb pail	TS19110 TS19150	10 lbs 50 lbs
EPOXY CATALYST Hastens initial set of 100% solids and solvent based epoxies.	6 fl oz per gal of mixed epoxy	16 fl oz per can (12/case)	8451ES-K54	1 lb

FLOOR REPAIR PRODUCTS

EPO-STONE EPOXY Fast-set epoxy. Sets in 3-4 hours. For <u>Crack Fill and Priming</u> ; Use liquids only; amber clear. <u>Patch and Overlay</u> ; Use liquids with aggregate; Gray or Natural Mortars.	Liquids: 75 linear ft @ 1/8" wide and 1" deep per .5 gal kit Mortar: 18 sq ft/5 gal kit @ 1/4"	.5 gal kit (liquids only)	82801-AB	8 lbs
		5 gal kit mortar (liquids and sand)	82810-G (gray) 82810-N (natural)	45 lbs 45 lbs
		5 gal kit mortar (liquids and sand)		
EPO-STONE XTRA FAST Faster setting version of EPO-STONE. Sets in 1-2 hours. Natural only.	4 sq ft @ 1/4 inch per kit	2 gal kit	82128-2	18 lbs
CON-KORITE X'TRA MORTAR Fast set high abrasion resistant formulation. Applies to damp concrete. Added chemical resistance when combined with KB25 RESIN. Use with or without KB25 RESIN (See SPECIAL ADDITIVES). Use SET CONTROL in warm weather to slow set time.	.5 cubic ft/55 lbs mortar, 25 sq ft @ 1/4" or 37.5 sq ft @ 1/4" extended with 25 lbs sand Sand extender can be used for medium duty applications.	60 lb KIT (24/pallet) (Kit includes 2 qt KB25 and 1 pouch SET CONTROL)	KB0100	65 lbs
		55 lb BAG (56/pallet)* 55 lb PAIL (36/pallet)* CR PACK (18/pallet) (Pack includes 1 gal KB25 and 1 pouch SET CONTROL) * KB25 RESIN and SET CONTROL ordered separately (See SPECIAL ADDITIVES)	KB0060 (6 min) KB0061 KB0065	55 lbs 55 lbs 70 lbs

EPOXY GEL Gel paste. Vaseline like consistency. Vertical/horizontal crack and hole fill. 100% solids rigid high performance epoxy.	150 linear ft @ 1/8" wide and 1" deep per gal	1 gal kit 2 gal kit	72821 72821-2	19 lbs 37 lbs
EPOXY JOINT FILL MEDIUM GRAY Urethane epoxy hybrid produces high-strength semi-ridged joint and crack fill. Pourable. Bonds to concrete and metal.	40 linear ft per gal @ 1/2" x 1"	1 gal kit (medium gray) 2 gal kit (medium gray)	72829 72829-2	14 lbs 28 lbs
EPOXY JOINT FILL VERTICAL MEDIUM GRAY Flexible epoxy paste for vertical and horizontal expansion joints and cracks. Bonds to concrete and metal.	40 linear ft per gal @ 1/2" x 1"	1 gal kit (medium gray) 2 gal kit (medium gray)	72829HV 72829HV-2	15 lbs 29 lbs

SPECIAL ADDITIVES

KB25 RESIN Acrylic polymer with high bonding properties. Adds moisture resistance and some chemical resistance properties to portland-based mortar mixes and CON-KORITE XTRA.	Typical use: one gallon for (3) 55 lb bags CON-KORITE mortar (using as both primer and admixture). Also can be used as a sealer at 200 sq ft per gallon. For the best resistance to chemicals use one gallon per 55 lb bag of CON-KORITE XTRA in place of water	2 qt (6/case) 1 gal (4/case) 5 gal pail	KB0025 KB0026 KB0027	5 lbs 10 lbs 50 lbs
SET CONTROL Use in warm weather to extend the working time of CON-KORITE XTRA.	Use 1 pouch per 55 lb bag to extend working time about 15 minutes. <u>Use up to 3 pouches.</u>	1 pouch	KB0001	2 oz

WALL COATINGS (BLOCK, POURED WALLS, WOOD & METAL SURFACES)

EPOXY BLOCK COATING Heavy bodied epoxy for block and poured walls. High build 100% solids epoxy. Exhibits excellent wear-ability. Gloss finish and very good color stability. Stand alone coating.	50-100 sq ft per gal @ 16-30 mils Apply two coats or one coat over a prime coat of EPO-SEAL HS VERTICAL for the most uniform gloss	1 gal kit (white) 5 gal kit (white) ♂ Other colors optional	AC505V AC505V-5	15 lbs 70 lbs
EPO-SEAL HS VERTICAL OFF WHITE Water-based, high solids wall coating with low odor and moisture tolerance. Very good gloss, color stability and wear properties.	250 sq ft/gal @ 5 mils Apply two coats for the most uniform gloss Used as a prime coat for EPOXY BLOCK COAT and ULTRA-GLOSS WALL COAT	2 gal kit (off white) 5 gal kit (off white) Other colors available	ES015V-2 ES015V-5	20 lbs 50 lbs
ULTRA-GLOSS WALL COAT Semi-gloss, high solids urethane with excellent vertical stability. Ultra-Gloss Wall Coat exhibits the same high quality properties as the floor coating version.	320 sq ft/gal @ 3 mils Apply two coats for the most uniform gloss or a single coat over EPO-SEAL HS VERTICAL	1.5 gal kit (white) 3 gal kit (white) Other colors available	UG320V UG320V-3	15 lbs 32 lbs

BIN AND ROOF COATINGS

ACRYLIC COATING Acrylic self-plasticizing monolithic coating. Flexible membrane withstands temperature extremes, UV light, foot traffic, water and mildew. Bonds to concrete and metal.	100 sq ft/gal/coat @ 30 mils	5 gal (white)	RC811FPW-5	58 lbs
		5 gal (beige)	RC811FPB-5	58 lbs
ACRYLIC CAULK Acrylic caulk fills voids, splits, seams, laps and bolt heads. Use prior to Acrylic Roof Coating. Bonds to concrete and metal.	13 sq ft/gal @ 1/8"	3.5 gal pail (white)	RC815M-3	42 lbs

PREPARATION CHEMICALS & CLEAN-UP SUPPLIES

VPC-49 DEEP KLEEN Removes grease, oil, many stains and dirt. Concentrate.	Up to 400 sq ft/gal	1 gal (4/case)	VPC-49-1	9 lbs
VP-151 CONCRETE CONDITIONER AND ETCH Removes soils, concrete laitance, mineral deposits and etches concrete surfaces in one step. Safer to use than muriatic acid.	100-300 sq ft/gal	1 gal (4/case) ♂	VP-151-1	10.5 lbs
		5 gal ♂	VP-151-5	45 lbs
VSC FLOOR STRIPPER 722 "Fast-working" stripper for stripping of paints, urethanes, curing compounds, epoxies and tile glue.	75-150 sq ft/gal	1 gal (4/case)	VP-722-1	12 lbs
		5 gal ♂	VP-722-5	60 lbs
SOLVENTS Excellent for clean up of epoxy on equipment and tools. Thinner for epoxies.	Variable	1 gal (4/case) SOLVENT 101	VPC-101-1	7 lbs
		5 gal SOLVENT 101 R	VPC-101-5	40 lbs
		1 gal (4/case) IPA R	VPC-IPA-1	9 lbs
		5 gal IPA R	VPC-IPA-5	50 lbs
EPOXY HAND CLEANER Safe cleaner removes tough epoxy and urethane residue from hands and tools.		8 oz tube	TSS81872	.5 lbs

MIXING EQUIPMENT

PROP MIXER Designed for thorough mixing of paints, epoxies, urethanes and mortars. Use with 1/2" variable speed electric drill.	Large 4" diameter prop, 18" long with 1/2" diameter shaft	1 unit	TS46565	4.3 lbs
PAIL MIXER 1/4 HP driven automatic mixer for easy and thorough mixing of EPO-STONE, ARMOR-GROUT, and EPOXY SLURRY mixes.	Mixing pail, arm, frame, and motor	1 unit	TSKM5825	40 lbs
	Extra arm	1 unit	TSKR2	1 lb
CONTAINERS Convenient mixing containers and lids for proper handling of epoxies and mortars	5 gal pail	1 unit	TS305	3 lbs
	Lid	1 unit	TS305L	1 lb
	Pour spout lid	1 unit	TS305PL	1 lb
	1 qt measuring pail	1 unit	TS1QM	.5 lb
	2 qt measuring pail	1 unit	TS2QM	.5 lb

BRUSHES, ROLLER COVERS, FRAMES, TRAYS AND TOOLS

CHIP BRUSHES Ideal for epoxy cut-in along edges and around equipment.	White china bristle with wood handle	3" brush	TSF5117-3	
18" WOOSTER PRO DOOZ ROLLER COVERS Lint-free and solvent resistant covers for applying high-tack and solvent-based coatings.		3/8" nap 18" wide 1/2" nap 18" wide	TSR642-18 TSR643-18	.5 lb .5 lb
9" WOOSTER SUPER DOOZ ROLLER COVERS Lint-free and solvent resistant covers for applying high-tack and solvent-based coatings.		3/8" nap 9" wide 1/2" nap 9" wide	TSR765-9 TSR204-9	.5 lb .5 lb
4" WOOSTER SUPER DOOZ ROLLER COVERS Lint-free and solvent resistant covers for applying high-tack and solvent-based coatings.		3/8" nap 4" wide 1/2" nap 4" wide	TSR205-4 TSR204-4	.25 lb .25 lb
LOOPED ROLLER COVER Plastic loops remove trapped air and levels epoxy coatings.		9" cover 18" cover	TSR233-9 TSR233-18	.5 lb 1 lb
9" HEAVY DUTY ROLLER FRAME 5/16" plated steel frame supports roller for heavy coat applications.		9" frame (uses threaded tip pole)	TSF0010-9	1.5 lbs
4" ROLLER FRAME		4" frame (uses threaded tip pole)	TSF0010-4	.25 lb
BIG BEN 18" ROLLER FRAME Provides economy and durability for larger products		18" frame (uses threaded tip pole) Replacement legs (1 pair)	TsBR045 TsBR085	1 lb 1 lb
5 or 6 FOOT WOOD HANDLE Universal threaded metal end.	Use with 9" and 18" roller frames	(1) 6 foot threaded tip pole (1) 5 foot threaded tip pole	TSF0004 TSF0005	1.5 lbs 1.5 lbs
1-3 FOOT POLE SET	Three 12" pieces assemble to 36 inch pole	(1) threaded tip pole pack	TSF0007-3	1.5 lbs
5 FOOT TAPERED POLE Heavy-duty pole. Use with serrated squeegee.	Use with serrated and flat-bladed squeegees	(1) 5 foot tapered pole	TSF0008	1.5 lb
9" and 18" ROLLER TRAYS Durable plastic tray that accommodates 9" and 18" roller frames.	Deep well 9" wide (2 quart tray) Big Ben 18" wide tray	(1) 9" tray (1) 18" tray	TSR404 TSBR412	1 lb 4 lbs
SPIKED SHOES Enables a person to walk over wet epoxy and urethane while coating floors	Polypropylene spiked shoes with 3/4" spikes	(1) pair (1) set of 26 extra 3/4" spikes (1) set of spare straps	TS46106 TS46125 TS46120	2 lbs 2 lbs .5 lb
NOTCHED SQUEEGEE 18" and 24" rubber squeegee with notches. Spreads epoxy liquids and slurry mixes uniformly.	3/8", 1/4" or 1/8" notches available Use with 5 ft tapered pole	18" notched squeegee 24" notched squeegee 18" squeegee (economy) 1/8" notches only* *Use with threaded tip poles	TS1418-SE TS1424-SE TSFEC-18N	2 lbs 3 lbs 2 lbs
6" NOTCHED SQUEEGEE 6" wide rubber squeegee with notches. Use for slats, wall edges and areas hard to access with larger squeegees.	3/8" notches available Use with 1-3 foot pole set	6" notched squeegee 6" notched squeegee with handle	TSFECSE-6 TSFECSE-6H	.5 lbs 2 lbs
FLAT-BLADED SQUEEGEE Economy. For uniform spreading of heavy coatings.	Use with 18" threaded poles Use with tapered pole	18" squeegee (flat - economy) 24" squeegee (flat - general duty)	TSFEC-18F TS024	1 lb 1 lb
EPO-STONE TROWELS Pre-ground rounded edges for smooth troweling of EPO-STONE epoxy mortars.	For large areas For small areas Cove trowel - 4"	14" x 3" 8" x 3" 4" x 3" x 6"	TSTC6C TST1MT TS47411	1 lb 1 lb 1 lb
NOTCHED TROWEL 1/8" or 1/4" notches for spreading ARMOR-ROCK and ARMOR-SLATE slurry epoxy systems.		11" x 4 1/2" x 1/8" notch 11" x 4 1/2" x 1/4" notch	TS110-33 TS110-77	1 lb 1 lb