

Kit Includes:

- ArmorCoat SUPRA Part "A"
- ArmorCoat SUPRA Part "B"
- Color Flakes
- Cleaner/Degreaser
- Non-Skid Additive
- Stir Stick
- Application Guide

Other Supplies Needed:

- 3/8" Roller Cover
- Roller Frame
- Extension Pole
- Protective Gloves & Glasses
- Push Broom


ARMORCOAT™ SUPRA

HIGH STRENGTH, PROFESSIONAL
GRADE WATERBORNE EPOXY

2 Application Options:



Medium Gray



Med. Gray w/Flakes



- Water Based
- Long Lasting

ARMORCOAT™ SUPRA

HIGH STRENGTH, PROFESSIONAL
GRADE WATERBORNE EPOXY



- Chemically Resistant
- Stain Resistant



- Hot Tire Resistant
- Soap & Water Cleanup



Part A—Epoxy Base Color

29.7 fl. oz. (0.93 qts) / 0.88 L

Part B—Activator

72.7 fl. oz. (2.27 qts) 2.15 L

Decorative Flakes

16 oz. / 0.45 kg

Cleaner/Degreaser

3.2 oz. / 0.09 kg

WARNING: This kit contains the following chemicals that may be harmful if misused: epoxy polymer, 2-propanol. Read cautions on individual containers carefully. Keep out of reach of children.



www.vanbergcoatings.com

800-874-0631



ARMORCOATTM SUPRA

HIGH STRENGTH, PROFESSIONAL GRADE WATERBORNE EPOXY

ARMORCOAT SUPRA is a unique blend of high solids pigmented epoxy that offers excellent adhesion and abrasion resistance. It outperforms and outlast most solvent-based sealer systems without the associated odors, flammability, or VOC's.

- Commercial
- Showrooms
- Pharmaceutical
- Service Centers
- Shops/Garages
- Warehouses
- Manufacturing
- Agricultural



www.vanbergcoatings.com

800-874-0631

The Coating that "BREATHES".

ARMORCOAT SUPRA water-based chemistry forms a unique coating that allows moisture vapor to pass through. Unlike other coatings, ARMORCOAT SUPRA resists blistering, chipping and peeling due to moisture pressure.

ARMORCOAT SUPRA

Partial Flake Kit: #AC5361G-K

Coverage: 200-250 square feet.

High Gloss Clear Top Coat exhibits high resistance to grease, oil, UV exposure:

EPO-KOTE High Gloss Clear
Top Coat (Optional)

1 Gallon: #E5046

Coverage: 300-400 square feet.

5 Simple Steps:

1



Clean surface.

2



Mix components.

3



Use roller to apply.

4



Broadcast flakes.
(Optional.)

5



Apply clear coat.
(Optional.)

EPO-KOTE Clear Top Coat (sold separately) provides an even tougher, glossy finish for ARMORCOAT SUPRA floors. Application is recommended for COLOR FLAKE floors in high traffic areas. EPO-KOTE should be applied with a 1/4" (6.4 mm) roller. It may be re-applied to maintain high gloss finish.

*Recommended coverage
is 320 sq. ft. per 1 gallon kit.*